

# VIPIR-2S

## Uncooled Thermal Imager Hand Held Thermal Surveillance Sight

**VIPIR-2S** is part of a family of compact and lightweight thermal sights utilising low power uncooled IR camera technology.

**VIPIR-2S** is a compact and lightweight military standard thermal sight designed specifically for medium-range surveillance and target observation.



### Features

- Low powered uncooled technology
- Compact and lightweight
- Fully qualified and ruggedised
- x2.7 magnification
- x2 electronic zoom
- 24 hour operational capability
- Suitable for short-medium range surveillance

# VIPIR-2S

## Hand Held Thermal Surveillance Sight

The fully ruggedised and qualified design offers image optimisation features and a 24 hour operational capability.

**VIPIR-2S** utilises uncooled thermal imaging technology to provide a superior performance to weight/size ratio.

The low power consumption of this technology allows VIPIR-2S to operate with only 4 commercially available AA batteries, greatly reducing through life costs.

**VIPIR-2S** controls include:

- Electronic zoom
- Aiming mark selection / adjustment
- Automatic and manual gain and level
- Polarity and display brightness



### Main features

<b>Magnification:</b> x2.7, x5.4 (electronic zoom)
<b>Field of View:</b> 9° HFOV
<b>Detection Range - Man:</b> x2.7 Mag – 1870m x5.4 Mag – 2090m
<b>Weight (excluding batteries &amp; weapon mount):</b> <990g
<b>Dimensions:</b> 270mm (L) x 100mm (W) x 78mm (H)
<b>Detector type:</b> 8 to 12µm, 320 x 240 pixels, 38µm pitch FPA
<b>Batteries:</b> 4 x 1.5V AA
<b>Battery Life:</b> >7 hours continuous operation @ 23°C – Lithium
<b>Features:</b> RS232 comms, Video out, External power source
<b>Accessories:</b> Tripod mount, Lens Cap, Carrying Pouch, Transit Case, Instruction Card, User Manual, Neck Strap, Lens Cleaning Kit
<b>Optional accessories:</b> Interface Cable (external power, serial communications & video)

**For technical information contact:**

Qioptiq Limited  
sales@uk.qioptiq.com  
phone +44 (0)1745 588000  
www.qioptiq.com

